

Automotive Chemicals – Technical Sprays - Assembly

Version: **TS/006**

Valvoline™ Copper Spray

High quality spray with a high copper content to prevent wear and sticking of screwed connections which are exposed to high temperatures.

Applications

Brake parts
Exhaust parts
Screwed connections, which are exposed to very high temperatures
Thread of spark plugs

Product characteristics

High thermal stability
Resistant to chemical and weather influences
Corrosion preventative
Excellent adhesion
Prevents wear and sticking
Simplifies the future removal
Directed jet spray

Easy to use:

Before use, carefully read the directions on the packaging.

Valvoline™ Copper Spray should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Apply Valvoline™ Copper Spray. The specific lubrication property is achieved after evaporation of the solvent (approx. 1 minute)

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Copper Spray	
Contents	500 ml
Basis	EP grease and small copper particles
VOC-content	Approx. 69% w/w
Solid content	Approx. 31% w/w
Colour	Copper
Scent	Characteristic
Appearance	Paste
Relative density at 20°C	0,767 g/ml
Yield	1,26 g/sec
Vapour pressure at 20°C	3 to 4 bar
Temperature resistant	-40°C to +1.100°C

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –