

Automotive Chemicals – Technical Sprays - Assembly

Version: **TS/009**

Valvoline™ Glue Spray

High quality glue for both permanent and temporary adhesion. Suitable to glue paper, cardboard, wood, textile and various types of plastics.

Applications

Paper
Wood
Cork
Cardboard
Textile
Leather
Various types of plastics

Product characteristics

Suitable to glue large surfaces
Fast drying
User friendly
Spray pattern about 10 centimetres wide

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Glue Spray should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Distance to the surface to be treated is approximately 25 to 30 centimetres.

Apply Valvoline™ Glue Spray in an equal layer.

For permanent adhesion, treat both parts to be glued and allow to dry for 15 to 20 minutes, after this press firmly together.

For temporary adhesion, treat one of the parts to be glued and allow to dry for 5 to 10 minutes, after this press firmly together.

When treating porous surfaces, apply several layers.

After use, clean the valve (turn spray can upside down and press the nozzle for approx. 5 seconds.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Glue Spray	
Contents	500 ml
Basis	Synthetic resin
VOC-content	Approx. 83% w/w
Solid content	Approx. 31% w/w
Colour	Transparent white
Scent	Characteristic
Relative density at 20°C	0,75 g/ml
Yield	1,2 g/sec
Vapour pressure at 20°C	3 to 4 bar
Heat resistant	to +80°C

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –