



## *Automotive Chemicals – Technical Sprays - Lubrication*

Version: **TS/005a**

# Valvoline™ Synthetic Chain Lube

Valvoline™ Synthetic Chain Lube is a lubricant to treat chains and sprockets of e.g. motorcycle, bicycles, mopeds, etc. Valvoline™ Synthetic Chain Lube has a low friction factor for minimal resistance while maintaining the outstanding lubricating properties, even at heavy loads. Especially suitable for high-speed chains.

### **Applications**

- For all types of (high speed) chain drives such as bicycles, motorcycles and mopeds

### **Product characteristics**

Low friction factor for minimal resistance  
Water-repellent  
Prevents wear  
Resistant to weather influences  
Reduces the adhesion of dirt

### Directions for use:

Carefully read and observe the warning text on the label.

Valvoline™ Synthetic Chain Lube should be at room temperature before use. The processing temperature should be between 5 to 30°C.

Shake before use.

Clean the chain and sprockets.

Apply Valvoline™ Synthetic Chain Lube in two thin and equal layers, while slowly rotating the chain.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Synthetic Chain Lube	
Contents	400 ml
Basis	Synthetic Oil
Colour	Transparent white
Scent	Characteristic
VOC-Content	Approx. 85% w/w
Relative density at 20°C	0,88 g/ml
Yield	1,5 to 2,0 g/sec
Vapour pressure at 20°C	Approx. 3 bar

**This information only applies to products manufactured in the following location(s): Europe**

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

## Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – TS/005