

Automotive Chemicals – Technical Sprays - Protection

Version: **TS/018**

Valvoline™ Electro Protect

High quality electro preservative to prevent starting problems caused by moisture.

Applications

Switches
Batteries
Multiple sockets
Cables
Electric tools
Plugs
Electric systems which should to be protected against moisture
Spark plugs
Printed circuit board switches
Distributor caps
Fuses
Current distributors

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Electro Protect should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Switch off electrical installations before treatment

Parts to be treated must be clean, dry and free of grease before using the product.

Apply Valvoline™ Electro Protect in several thin layers for the best result.

Product characteristics

Water/ Moisture repellent
Good penetrating properties
Excellent corrosion prevention properties
Excellent adhesion properties
360° valve

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

| Valvoline™ Electro Protect | |
|----------------------------|-----------------|
| Contents | 500 ml |
| Basis | Mineral Oil |
| VOC-content | Approx. 85% w/w |
| Colour | Transparent |
| Scent | Characteristic |
| Relative density at 20°C | 0,802 g/ml |
| Yield | 1,9 g/sec |
| Refractive Index at 20°C | 1,444 |
| Vapour pressure at 20°C | 3 to 4 bar |
| pH-value | Neutral |

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –