

Automotive Chemicals – Technical Sprays - Protection

Version: **TS/016**

Valvoline™ V-Belt Spray

High quality spray to protect V-Belts and prevent them from slipping.

Applications

Vehicles
Conveyer belts
Drill presses
Lathes
Generators
Forklift trucks
Milling machines
Machinery
Agricultural Machinery
Concrete mixers
Lawn mowers
Compressors
Pumps

Product characteristics

User friendly
Remedies and prevents slipping and creaking
Excellent adhesion properties
Lasting protection
Dilatant
Resistant to weather influences
Conditions V-Belts
Delays the wear of V-Belts
Directed jet spray

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ V-Belt Spray should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Switch off engine.

Apply Valvoline™ V-Belt Spray in an equal, thin layer on the threads of the V-Belt and allow to take effect.

After evaporation of the product, the engine can be switched on.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ V-Belt Spray	
Contents	500 ml
Basis	Polyalphaolefine
VOC-content	Approx. 93% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0,89 g/ml
Yield	1,15 g/sec
Vapour pressure at 20°C	3 to 4 bar

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –