



*Automotive Chemicals – Technical Sprays - Tool*

Version: **TS/004**

## **Valvoline™ Zinc Spray**

High quality zinc spray to treat galvanized and untreated steel.

---

### **Product characteristics**

Fast drying  
Good filling properties  
Outstanding cathodic corrosion prevention  
Resistant to petrol, chemicals and weather influences  
Spot-weldable  
Excellent adhesion

### Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Zinc Spray should be at room temperature before use. The processing temperature should be between 15 to 25°C. Shake 2 minutes before use and spray a sample.

### Pre-treatment:

The surface to be treated should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface

### Treatment:

When spraying, the distance between the spray and the surface should be approx. 25 to 30 centimetres.

Apply the spray in several thin layers. Before applying the next layer, shake the spray can.

When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approx. 5 seconds).

The drying time depends on the ambient temperature, the air humidity and the thickness of the lacquer applied.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Zinc Spray	
Contents	400 ml
Basis	Epoxy-ester
Colour	Grey
VOC-content (w/w%)	Approx. 54
Solid content (w/w%)	Approx. 46
Coverage (m <sup>2</sup> )	1,25 to 1,75
Dust dry	After 10 to 15 minutes
Tack free	After 20 to 30 minutes
Hardened/ re-sprayable	After 24 hours
Heat resistant	to 350°C

**This information only applies to products manufactured in the following location(s): Europe**

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

## Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –